NSN 5962-00-175-8964

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/hsh/5962-00-175-6964
Body Length:
Between 0.240 inches and 0.390 inches
Body Width:
Between 0.140 inches and 0.270 inches
Body Height:
Between 0.030 inches and 0.090 inches
Maximum Power Dissipation Rating:
100.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hybrid and hermetically sealed and negative outputs and positive outputs and high speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
2 channel
Design Function And Quantity:
1 switch, analog
Terminal Surface Treatment:
Tin
Voltage Rating And Type Per Characteristic:
-45.0 volts power source and 45.0 volts power source
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
99974-st7890100 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0