NSN 5962-00-175-8964

Linear Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/hsh/5962-00-175-6964 |
|---|
| Body Length: |
| Between 0.240 inches and 0.390 inches |
| Body Width: |
| Between 0.140 inches and 0.270 inches |
| Body Height: |
| Between 0.030 inches and 0.090 inches |
| Maximum Power Dissipation Rating: |
| 100.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hybrid and hermetically sealed and negative outputs and positive outputs and high speed |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Input Circuit Pattern: |
| 2 channel |
| Design Function And Quantity: |
| 1 switch, analog |
| Terminal Surface Treatment: |
| Tin |
| Voltage Rating And Type Per Characteristic: |
| -45.0 volts power source and 45.0 volts power source |
| Time Rating Per Chacteristic: |
| 20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 99974-st7890100 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 14 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0