# NSN 5962-00-179-2934

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-179-2934

# **Body Length:**

Between 0.340 inches and 0.440 inches

# **Body Width:**

Between 0.265 inches and 0.325 inches

# **Body Height:**

Between 0.030 inches and 0.075 inches

# Maximum Power Dissipation Rating:

625.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

**End Application:** 

58404091248

#### Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and programmable and programmed and bipolar

and w/buffered output and w/decoded output and expandable and wire-or outputs

#### **Inclosure Material:**

Ceramic and glass

#### **Inclosure Configuration:**

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

6 input

#### **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

5.5 volts power source

## **Time Rating Per Chacteristic:**

50.00 nanoseconds propagation delay time, low to high level output

#### Memory Device Type:

Rom

#### Test Data Document:

05869-717383 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Terminal Type And Quantity:

16 flat leads

# Shelf Life:

N/a

#### Unit Of Measure:

# Demilitarization:

Yes - demil/mli

# NSN 5962-00-179-2934

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

