# NSN 5962-00-180-4204

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-180-4204

#### **Body Length:**

Between 0.660 inches and 0.785 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

800.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic and hermetically sealed and negative outputs and positive outputs and low power and adjustable

#### **Inclosure Material:**

## Ceramic and glass

Inclosure Configuration:

Dual-in-line

#### **Input Circuit Pattern:**

Dual 2 input

### **Design Function And Quantity:**

2 amplifier, operational, general purpose

## Case Outline Source And Designator:

T0-116 joint electron device engineering council

### **Terminal Surface Treatment:**

Gold

#### **Time Rating Per Chacteristic:**

300.00 nanoseconds propagation delay time, low to high level output

#### **Precious Material And Location:**

Terminals gold and body gold

#### **Precious Material:**

Gold

# Test Data Document:

95750-17007150 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0