NSN 5962-00-188-9885

Memory Microcircuit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5962-00-188-9885 |
|---|
| Body Length: |
| Between 0.340 inches and 0.440 inches |
| Body Width: |
| Between 0.265 inches and 0.325 inches |
| Body Height: |
| Between 0.030 inches and 0.075 inches |
| Maximum Power Dissipation Rating: |
| 625.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+75.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 58404091248 |
| Features Provided: |
| Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable and programmable and programmed and bipolar |
| and w/buffered output and w/decoded output and expandable and wire-or outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 6 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 50.00 nanoseconds propagation delay time, low to high level output |
| Memory Device Type: |
| Rom |
| Memory Capacity: |
| Unknown |
| Test Data Document: |
| 05869-717383 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |

N/a

16 flat leads Shelf Life:

Unit Of Measure:

Terminal Type And Quantity:

NSN 5962-00-188-9885

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0