# NSN 5962-00-190-1746

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-190-1746

## **Body Length:**

Between 0.750 inches and 0.795 inches

## **Body Width:**

Between 0.245 inches and 0.300 inches

## **Body Height:**

Between 0.120 inches and 0.195 inches

## **Maximum Power Dissipation Rating:**

341.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and medium power and medium speed and w/decoded output

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

## Input Circuit Pattern:

4 input

#### **Design Function And Quantity:**

1 decoder, binary coded decimal to decimal and 1 decoder, binary coded decimal to one of ten

#### Case Outline Source And Designator:

-0-001-ag joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

5.5 volts power source

#### **Time Rating Per Chacteristic:**

46.00 nanoseconds propagation delay time, low to high level output and 46.00 nanoseconds propagation delay time, high to low level

output

#### **Terminal Type And Quantity:**

16 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0