NSN 5962-00-190-1864

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-190-1864

view Offiline at https://aerobasegroup.com/nsn/3302-00-130-1004
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
99.4 milliwatts
Operating Tempurature Range:
-55.0 to 125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Darlington-connected and high speed and monolithic and positive outputs and w/totem pole output and low power
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 gate, nor
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
13.00 nanoseconds propagation delay time, low to high level output and 13.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0