## NSN 5962-00-190-1873

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-190-1873
Body Length:
Between 0.240 inches and 0.290 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and externally compensated and positive outputs and negative outputs and externally compensated and adjustable
Inclosure Material:
Glass and metal
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
T0-91 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Time Rating Per Chacteristic:
50000.00 nanoseconds propagation delay time, low to high level output and 60000.00 nanoseconds propagation delay time, high to low
level output
Precious Material And Location:
Terminals gold and body gold
Precious Material:
Gold
Terminal Type And Quantity:
10 flat leads
Shelf Life:

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

N/a

## NSN 5962-00-190-1873

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0