NSN 5962-00-197-3430



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-197-3430 **Body Outside Diameter:** Between 0.335 inches and 0.370 inches **Body Height:** Between 0.165 inches and 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -25.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and w/strobe and adjustable **Inclosure Material:** Glass and metal **Inclosure Configuration:** Can **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 comparator, voltage, differential **Case Outline Source And Designator:** T0-99 joint electron device engineering council **Terminal Surface Treatment:** Gold **Time Rating Per Chacteristic:** 500.00 nanoseconds propagation delay time, low to high level output and 2000.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals gold **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0