NSN 5962-00-197-3540

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-197-3540

Body Length:

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

180.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+175.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and negative outputs and high speed and internally compensated and ac coupled and w/enable and

resettable and edge triggered

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Emitter-coupled logic

Input Circuit Pattern:

Dual 5 input

Design Function And Quantity:

2 flip-flop, j-k/r-s, clocked

Case Outline Source And Designator:

T0-116 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-10.0 volts power source and 0.0 volts power source

Time Rating Per Chacteristic:

4.50 nanoseconds propagation delay time, low to high level output

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0