NSN 5962-00-197-3541

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5062-00-107-35/1

| View Online at https://aerobasegroup.com/nsn/5962-00-197-3541 |
|---|
| Body Length: |
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 140.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+175.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and negative outputs and high speed and internally compensated |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Design Function And Quantity: |
| 3 amplifier, differential and 2 schmitt trigger |
| Case Outline Source And Designator: |
| T0-116 joint electron device engineering council |
| Terminal Surface Treatment: |
| Tin |
| Voltage Rating And Type Per Characteristic: |
| -10.0 volts power source and 0.0 volts pac identification output |
| Time Rating Per Chacteristic: |
| 5.00 nanoseconds propagation delay time, low to high level output |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| part (|

Fiig:

A458a0