## NSN 5962-00-199-4072

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-199-4072 **Body Length:** 0.870 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 105.0 milliwatts **Operating Tempurature Range:** -40.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius **Features Provided:** Monolithic and positive outputs and w/decoded output and high voltage **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 decoder, one of ten line and 1 driver, nixie **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -1.5 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 89944-68201022301 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

A458a0

Fiig:

**Demilitarization:** Yes - demil/mli