NSN 5962-00-200-9660

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-200-9660

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and w/strobe
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 channel
Design Function And Quantity:
2 comparator, voltage, differential
Case Outline Source And Designator:
T0-100 joint electron device engineering council
Terminal Surface Treatment:
Tin
Voltage Rating And Type Per Characteristic:
-7.0 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
05869-710398-19 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:

A458a0