NSN 5962-00-202-9570

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-202-9570

| View Online at https://aerobasegroup.com/nsn/5962-00-202-9570 |
|---|
| Body Length: |
| Between 0.660 inches and 0.785 inches |
| Body Width: |
| Between 0.220 inches and 0.280 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 600.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and positive outputs and negative outputs and w/strobe and medium speed |
| Inclosure Material: |
| Glass and metal |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| Dual 4 input |
| Design Function And Quantity: |
| 2 receiver, line differential |
| Case Outline Source And Designator: |
| T0-116 joint electron device engineering council |
| Terminal Surface Treatment: |
| Gold |
| Time Rating Per Chacteristic: |
| 150.00 nanoseconds propagation delay time, low to high level output |
| Precious Material And Location: |
| Terminals gold and body gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 22915-2-114 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A458a0