NSN 5962-00-202-9570

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-202-9570

View Online at https://aerobasegroup.com/nsn/5962-00-202-9570
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
600.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and negative outputs and w/strobe and medium speed
Inclosure Material:
Glass and metal
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 receiver, line differential
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
150.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminals gold and body gold
Precious Material:
Gold
Test Data Document:
22915-2-114 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A458a0