NSN 5962-00-209-5213

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-209-5213 **Overall Height:** 0.330 inches **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** 0.280 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 10.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nor **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 22.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 5962-00-209-5213Digital Microcircuit - Page 2 of 2



Fiig:

A458a0