## NSN 5962-00-209-6805

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-209-6805

| Body Outside Diameter:  |
|---|
| Between 0.335 inches and 0.370 inches   |
| Body Height:  |
| Between 0.165 inches and 0.185 inches   |
| Maximum Power Dissipation Rating:   |
| 600.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Low noise and hermetically sealed and wideband  |
| Inclosure Material:   |
| Metal and glass   |
| Inclosure Configuration:  |
| Can   |
| Input Circuit Pattern:  |
| Dual 1 channel  |
| Design Function And Quantity:   |
| 2 array, darlington transistor  |
| Case Outline Source And Designator:   |
| T0-5 joint electron device engineering council  |
| Terminal Surface Treatment:   |
| Tin   |
| Special Features:   |
| Only ten leads required   |
| Test Data Document:   |
| 10001-2832812 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
| Fiig:   |
| A458a0  |
|   |