NSN 5962-00-220-3072

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-220-3072 **Body Length:** Between 0.660 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hybrid and hermetically sealed and positive outputs and negative outputs and externally compensated **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 amplifier, operational, general purpose **Case Outline Source And Designator:** T0-116 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

19315-1907394 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-00-220-3072

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0