## NSN 5962-00-222-6837

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-222-6837

о.	- d		nath:	
nı	mw	1 6		-

Between 0.755 inches and 0.790 inches

**Body Width:** 

Between 0.265 inches and 0.300 inches

**Body Height:** 

Between 0.155 inches and 0.175 inches

## **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

## **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

## **End Application:**

Type angyk3v coordinate data terminal

#### **Features Provided:**

Monolithic and hermetically sealed and positive outputs and w/storage and w/enable and schottky and w/decoded output and presettable and programmable and w/open collector and programmed

## **Inclosure Material:**

Ceramic and glass

## **Inclosure Configuration:**

Dual-in-line

## **Output Logic Form:**

Transistor-transistor logic

## **Input Circuit Pattern:**

10 input

#### **Terminal Surface Treatment:**

Solder

## **Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

## **Time Rating Per Chacteristic:**

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

## **Memory Device Type:**

Rom

## **Memory Capacity:**

Unknown

## **Test Data Document:**

08241-1742-2874 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

16 printed circuit

## Shelf Life:

N/a

## **Unit Of Measure:**

--

## Demilitarization:

Vec - demil/mli

# NSN 5962-00-222-6837

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0