NSN 5962-00-223-5388

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-223-5388 **Overall Height:** 0.330 inches **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** 0.280 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 37.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Radio test set an/arm156 **Features Provided:** Hermetically sealed and monolithic and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, exclusive or **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-00-223-5388

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0