## NSN 5962-00-229-3876

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-229-3876

Bedween 0.755 inches and 0.785 inches Body Width: Between 0.245 inches and 0.280 inches Body Height: 0.180 inches Operating Tempurature Range: +0.0470.0 degrees celsius Storage Tempurature Range: +55.04150.0 degrees celsius Features Provided: Hermetically sealed and medium speed and w/totem pole output Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-ine Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: +1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: Na Unit Of Measure: Demilitarization: Yes - demili/mli	
Betwen 0.245 inches and 0.280 inches  Body Height:  0.180 inches  Operating Tempurature Range: +0.0/470.0 degrees celsius  Storage Tempurature Range: +0.0/470.0 degrees celsius  Storage Tempurature Range: +0.0/470.0 degrees celsius  Features Provided: Hermetically sealed and medium speed and w/totem pole output Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solider Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Tests Data Document: 49956-395710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14976-1410 Terminal Type And Quantit	Body Length:
Beween 0.245 inches and 0.280 inches  Body Height: 0.180 inches  Operating Tempurature Range: +0.0/+70.0 degrees celsius  Storage Tempurature Range: +65.0/+150.0 degrees celsius  Features Provided: Hermetically sealed and medium speed and whotem pole output Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Onfiguration: Dual-in-line  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solider  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: Nia Unit Of Measure: Demilitarization: Yes - demili/mli	Between 0.755 inches and 0.785 inches
Body Height:  0.180 inches Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: +0.0/+70.0 degrees celsius Features Provided: Hermetically sealed and medium speed and w/totem pole output Inclosure Material: Ceramic Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Body Width:
Operating Tempurature Range:  +0.0/+70.0 degrees celsius  Storage Tempurature Range:  -65.0/+150.0 degrees celsius  Features Provided:  Hermetically sealed and medium speed and whotem pole output  Inclosure Material:  Ceramic  Inclosure Configuration:  Dual-in-line  Output Logic Form:  Transistor-transistor logic  Input Circuit Pattern:  Quad 2 input  Design Function And Quantity:  4 gate, nand  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -1.5 volts power source and 5.5 volts power source  Test Data Document:  49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;  excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  14 printed circuit  Shelf Life:  Na  Unit Of Measure:  — Demilitarization:  Yes - demil/mli	Between 0.245 inches and 0.280 inches
Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and medium speed and w/totem pole output Inclosure Material: Ceramic Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure:	Body Height:
+0.0/470.0 degrees celsius  Storage Tempurature Range: -65.0/4150.0 degrees celsius  Features Provided: Hermetically sealed and medium speed and w/totem pole output Inclosure Material: Ceramic  Inclosure Material: Ceramic  Inclosure Configuration: Dual-in-line  Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input  Design Function And Quantity: 4 gate, nand  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mil	0.180 inches
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and medium speed and whotem pole output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Operating Tempurature Range:
-65.0+150.0 degrees celsius  Features Provided: Hermetically sealed and medium speed and w/totem pole output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	+0.0/+70.0 degrees celsius
Features Provided: Hermetically sealed and medium speed and whotem pole output Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Storage Tempurature Range:
Hermetically sealed and medium speed and w/totem pole output  Inclosure Material: Ceramic  Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	-65.0/+150.0 degrees celsius
Inclosure Material: Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Features Provided:
Ceramic Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Hermetically sealed and medium speed and w/totem pole output
Inclosure Configuration:  Dual-in-line  Output Logic Form:  Transistor-transistor logic  Input Circuit Pattern:  Quad 2 input  Design Function And Quantity: 4 gate, nand  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	Inclosure Material:
Dual-in-line  Output Logic Form:  Transistor-transistor logic  Input Circuit Pattern:  Quad 2 input  Design Function And Quantity: 4 gate, nand  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document:  49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life:  N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	Ceramic
Output Logic Form:  Transistor-transistor logic  Input Circuit Pattern:  Quad 2 input  Design Function And Quantity: 4 gate, nand  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document:  49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	Inclosure Configuration:
Transistor-transistor logic Input Circuit Pattern: Quad 2 input Design Function And Quantity: 4 gate, nand Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Dual-in-line
Input Circuit Pattern:  Quad 2 input  Design Function And Quantity: 4 gate, nand  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	Output Logic Form:
Quad 2 input  Design Function And Quantity: 4 gate, nand  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	Transistor-transistor logic
Design Function And Quantity: 4 gate, nand  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure: Demilitarization: Yes - demil/mli	Input Circuit Pattern:
4 gate, nand  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	Quad 2 input
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 14 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Design Function And Quantity:
Solder  Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	4 gate, nand
Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a  Unit Of Measure:  Demilitarization: Yes - demil/mli	Terminal Surface Treatment:
-1.5 volts power source and 5.5 volts power source  Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Solder
Test Data Document: 49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity: 14 printed circuit  Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Voltage Rating And Type Per Characteristic:
49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  14 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli	-1.5 volts power source and 5.5 volts power source
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Terminal Type And Quantity:  14 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli	Test Data Document:
Terminal Type And Quantity:  14 printed circuit  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli	49956-385710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
14 printed circuit  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  Yes - demil/mli	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:  N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli	14 printed circuit
Unit Of Measure: Demilitarization: Yes - demil/mli	Shelf Life:
Demilitarization:  Yes - demil/mli	N/a
Yes - demil/mli	Unit Of Measure:
Yes - demil/mli	
	Demilitarization:
Fiig:	Yes - demil/mli
	Fiig:
A458a0	A458a0