## NSN 5962-00-229-8500

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-229-8500

## **Body Length:**

Between 0.660 inches and 0.785 inches

## **Body Width:**

Between 0.220 inches and 0.280 inches

## **Body Height:**

Between 0.140 inches and 0.180 inches

## **Maximum Power Dissipation Rating:**

240.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic and positive outputs and w/open collector

#### Inclosure Material:

Plastic

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Hex 1 input

#### **Design Function And Quantity:**

6 inverter, digital

#### **Case Outline Source And Designator:**

T0-116 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

#### Time Rating Per Chacteristic:

55.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level

#### output

## **Precious Material And Location:**

Terminals silver

#### **Precious Material:**

Silver

#### **Terminal Type And Quantity:**

14 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5962-00-229-8500

Digital Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

