NSN 5962-00-231-4936

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-231-4936

Body Outside Diameter: Detween 0.598 inches and 0.604 inches Body Height: 0.270 inches Maximum Power Dissipation Rating: 900.0 millivants Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Storage Tempurature Range: -66.0/+150.0 degrees celsius Freatures Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: Na Unit of Measure:	
Body Height: 0.270 inches Maximum Power Dissipation Rating: 900.0 milliwatis Operating Tempurature Range: -55.07+125.0 degrees celsius Storage Tempurature Range: -56.07+125.0 degrees celsius Storage Tempurature Range: -56.07+125.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 plorit electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Sheft Life: Na Unit of Measure: Demilitarization: Yes - demil/mil Flig:	Body Outside Diameter:
0.270 inches Maximur Power Dissipation Rating: 900.0 millivratts Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+155.0 degrees celsius Storage Tempurature Range: -65.0/+155.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit of Measure: Demilitarization: Yes - demilmil Flig:	Between 0.598 inches and 0.604 inches
Maximum Power Dissipation Rating: 900.0 milliwatts Operating Tempurature Range: -55.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To 8- joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Sheff Life: Na Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	Body Height:
Operating Tempurature Range: -55.04-125.0 degrees celsius Storage Tempurature Range: -65.04-150.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Material: Metal Inclosure Material: Metal Inclosure Material: Posign Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mii Flig:	0.270 inches
Operating Tempurature Range: -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Configuration: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli Fiig:	Maximum Power Dissipation Rating:
-5.0/+125.0 degrees celsius Storage Tempurature Range: -6.5.0/+150.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli Flig:	900.0 milliwatts
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: TO-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mili Flig:	Operating Tempurature Range:
-65.0+150.0 degrees celsius Features Provided: Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: To-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 048481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mil Filg:	-55.0/+125.0 degrees celsius
Features Provided: Hermetically sealed and hybrid and monolithic and bum in Inclosure Material: Metal Inclosure Configuration: Can Imput Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mil Flig:	Storage Tempurature Range:
Hermetically sealed and hybrid and monolithic and burn in Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: Via Unit Of Measure: Demilitarization: Yes - demil/mli Flig:	-65.0/+150.0 degrees celsius
Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Features Provided:
Metal Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: 70-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Hermetically sealed and hybrid and monolithic and burn in
Inclosure Configuration: Can Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: TO-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic:	Inclosure Material:
Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: TO-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 0eX81-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Metal
Input Circuit Pattern: 2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Inclosure Configuration:
2 input Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Can
Design Function And Quantity: 1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Input Circuit Pattern:
1 regulator, voltage Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	2 input
Case Outline Source And Designator: T0-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Design Function And Quantity:
To-8 joint electron device engineering council Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1 regulator, voltage
Terminal Surface Treatment: Tin Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Case Outline Source And Designator:
Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	T0-8 joint electron device engineering council
Voltage Rating And Type Per Characteristic: -15.0 volts power source and 15.0 volts power source Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Surface Treatment:
Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Tin
Test Data Document: 06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Voltage Rating And Type Per Characteristic:
06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	-15.0 volts power source and 15.0 volts power source
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Test Data Document:
Terminal Type And Quantity: 12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	06481-970511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
12 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	12 pin
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
	Yes - demil/mli
A458a0	Fiig:
	A458a0