## NSN 5962-00-232-6915

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-232-6915

## **Body Length:**

Between 0.755 inches and 0.785 inches

## Body Width:

Between 0.265 inches and 0.291 inches

## **Body Height:**

Between 0.159 inches and 0.199 inches

## **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Type angyk3v coordinate data terminal

## **Features Provided:**

Hermetically sealed and monolithic and positive outputs and bipolar and programmable and programmed and w/buffered output and

w/decoded output and w/enable and w/open collector

#### **Inclosure Material:**

Ceramic and glass

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

10 input

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

## Time Rating Per Chacteristic:

60.00 nanoseconds propagation delay time, low to high level output

#### Memory Device Type:

Rom

#### **Memory Capacity:**

Unknown

#### **Test Data Document:**

08241-1742-3187 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

16 printed circuit

## Shelf Life:

N/a

#### Unit Of Measure:

Demilitarization:

Yes - demil/mli

# NSN 5962-00-232-6915

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

