## NSN 5962-00-232-6999

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-232-6999

о.	- d		nath:	
nı	mw	1 6		-

Between 0.755 inches and 0.785 inches

**Body Width:** 

Between 0.265 inches and 0.291 inches

**Body Height:** 

Between 0.159 inches and 0.199 inches

## **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

### **End Application:**

Type angyk3v coordinate data terminal

## **Features Provided:**

Hermetically sealed and monolithic and positive outputs and bipolar and programmable and programmed and w/buffered output and w/decoded output and w/enable and w/open collector

#### **Inclosure Material:**

Ceramic and glass

## **Inclosure Configuration:**

Dual-in-line

## **Output Logic Form:**

Transistor-transistor logic

### **Input Circuit Pattern:**

10 input

### **Terminal Surface Treatment:**

Solder

## **Voltage Rating And Type Per Characteristic:**

-1.5 volts power source and 5.5 volts power source

### **Time Rating Per Chacteristic:**

60.00 nanoseconds propagation delay time, low to high level output

## **Memory Device Type:**

Rom

## **Memory Capacity:**

Unknown

## **Test Data Document:**

08241-1745-2178 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

16 printed circuit

## Shelf Life:

N/a

## **Unit Of Measure:**

--

## **Demilitarization:**

Yes - demil/mli

# NSN 5962-00-232-6999

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0