## NSN 5962-00-234-1898

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-234-1898 **Body Length:** Between 0.255 inches and 0.275 inches **Body Width:** Between 0.365 inches and 0.385 inches **Body Height:** Between 0.045 inches and 0.065 inches **Maximum Power Dissipation Rating:** 100.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hybrid and hermetically sealed and positive outputs and negative outputs and w/buffered output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 amplifier, hybrid **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.0 volts power source **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Test Data Document:** 30003-247as-c0370 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig:

A458a0

Yes - demil/mli