NSN 5962-00-234-7284

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-234-7284

Body Length:

Between 0.240 inches and 0.260 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

0.070 inches

Maximum Power Dissipation Rating:

450.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs and programmable

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Output Logic Form:

Diode logic

Input Circuit Pattern:

8 input

Case Outline Source And Designator:

To-86 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

1.5 volts power source

Time Rating Per Chacteristic:

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-00-234-7284

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

