NSN 5962-00-234-7286

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-234-7286 **Body Length:** Between 0.240 inches and 0.260 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.070 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic and programmable and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Diode logic **Input Circuit Pattern:** 8 input **Case Outline Source And Designator:** To-86 joint electron device engineering council **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 1.5 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

N/a **Unit Of Measure:**

14 flat leads Shelf Life:

Terminal Type And Quantity:

NSN 5962-00-234-7286

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0