

View Online at <https://aerobasegroup.com/nsn/5962-00-235-9473>

**Body Length:**

Between 0.240 inches and 0.275 inches

**Body Width:**

Between 0.160 inches and 0.185 inches

**Body Height:**

Between 0.030 inches and 0.070 inches

**Maximum Power Dissipation Rating:**

176.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and medium power

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 gate, nand

**Case Outline Source And Designator:**

T0-85 joint electron device engineering council

**Time Rating Per Characteristic:**

10.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level output

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Test Data Document:**

17863-7118022 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0