

View Online at <https://aerobasegroup.com/nsn/5962-00-236-0319>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed and w/buffered output and internally compensated

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Input Circuit Pattern:

4 input

Criticality Code Justification:

Featg

Design Function And Quantity:

1 amplifier, wideband

Case Outline Source And Designator:

T0-99 joint electron device engineering council

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Time Rating Per Characteristic:

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

Special Features:

Static electricity sensitive

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0