NSN 5962-00-237-6094

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-237-6094

Body Length:
Between 0.330 inches and 0.350 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
0.065 inches
Maximum Power Dissipation Rating:
250.0 milliwatts
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs
nclosure Material:
Ceramic
nclosure Configuration:
Flat pack
Output Logic Form:
Diode-transistor logic
nput Circuit Pattern:
2 input
Design Function And Quantity:
1 multivibrator, monostable
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level
putput
Special Features:
Formed leads
Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Test Data Document:
00752-332512 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
-

Fiig:

A458a0

Demilitarization: Yes - demil/mli