# NSN 5962-00-240-5857

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-240-5857

Body Length:
Between 0.330 inches and 0.350

) inches

**Body Width:** 

Between 0.240 inches and 0.260 inches

**Body Height:** 

Between 0.049 inches and 0.065 inches

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+200.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and high speed and monolithic and negative edge triggered and positive outputs and presettable and resettable and w/enable and w/strobe

#### **Inclosure Material:**

Ceramic and glass

#### **Inclosure Configuration:**

Flat pack

#### **Output Logic Form:**

Transistor-transistor logic

#### **Input Circuit Pattern:**

8 input

#### **Design Function And Quantity:**

1 counter, binary

# **Terminal Surface Treatment:**

Gold

# Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

#### **Time Rating Per Chacteristic:**

42.00 nanoseconds propagation delay time, low to high level output and 42.00 nanoseconds propagation delay time, high to low level output

#### **Precious Material And Location:**

Terminals gold

#### **Precious Material:**

Gold

#### **Test Data Document:**

13499-351-7542 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Terminal Type And Quantity:**

14 flat leads

### Shelf Life:

N/a

#### **Unit Of Measure:**

# Demilitarization:

Voc. domil/mli

# **NSN 5962-00-240-5857**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0