## NSN 5962-00-240-6144

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-240-6144
Body Length:
Between 0.710 inches and 0.770 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
130.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and positive outputs and medium power and medium speed
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Design Function And Quantity:
2 gate, nor
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
25.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
$01749 - 3005662 \ drawing \ (this is the basic governing \ drawing, \ such as a contractor \ drawing, \ original \ equipment \ manufacturer \ drawing, \ etc.;$
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0