# NSN 5962-00-241-3800

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-241-3800

Body	Length:
------	---------

Between 0.660 inches and 0.785 inches

**Body Width:** 

Between 0.220 inches and 0.280 inches

**Body Height:** 

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:** 

100.0 milliwatts

### **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

### **Storage Tempurature Range:**

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic and hermetically sealed and asynchronous and edge triggered and high speed and positive outputs and synchronous and w/clear and w/enable

#### **Inclosure Material:**

Ceramic and glass

### **Inclosure Configuration:**

Dual-in-line

# **Output Logic Form:**

Transistor-transistor logic

### **Input Circuit Pattern:**

10 input

### **Design Function And Quantity:**

1 flip-flop, j-k, clocked and 1 flip-flop, j-k, master slave

# **Case Outline Source And Designator:**

T0-116 joint electron device engineering council

# **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 5.5 volts power source

# **Time Rating Per Chacteristic:**

20.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

# **Terminal Type And Quantity:**

14 printed circuit

# Shelf Life:

N/a

# **Unit Of Measure:**

### **Demilitarization:**

Yes - demil/mli

# Fiig:

A458a0