## NSN 5962-00-243-0375

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-243-0375

view Online at https://aerobasegroup.com/nsn/5962-00-243-0375
Body Length:
Between 0.330 inches and 0.350 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
236.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, exclusive or
Case Outline Source And Designator:
T0-88 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
82577-932444 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** Yes - demil/mli

## **NSN 5962-00-243-0375**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0