# NSN 5962-00-243-2496

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-243-2496

## **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

## **Body Height:**

Between 0.165 inches and 0.185 inches

## Maximum Power Dissipation Rating:

500.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Monolithic and hermetically sealed and high gain and wire-or outputs and low power and negative outputs and positive outputs

#### **Inclosure Material:**

Glass and metal

## Inclosure Configuration:

## Input Circuit Pattern:

Dual 2 input

Can

## **Design Function And Quantity:**

2 amplifier, audio frequency and 2 amplifier, preamplifier

## Case Outline Source And Designator:

T0-99 joint electron device engineering council

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

12.0 volts power source

## **Time Rating Per Chacteristic:**

300.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output

## **Terminal Type And Quantity:**

8 pin

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

## Fiig:

A458a0