NSN 5962-00-248-2667

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-248-2667

View Online at https://aerobasegroup.com/nsn/5962-00-248-2667
Body Length:
Between 0.330 inches and 0.350 inches
Body Width:
Between 0.200 inches and 0.300 inches
Body Height:
Between 0.008 inches and 0.100 inches
Maximum Power Dissipation Rating:
25.2 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+200.0 degrees celsius
Features Provided:
Hermetically sealed and expandable and monolithic and positive outputs and w/totem pole output and low power
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 gate, nand-nor
Case Outline Source And Designator:
-0-004-aa joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig: A458a0

Yes - demil/mli