## NSN 5962-00-252-4530

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-252-4530

Body Length:
Between 0.745 inches and 0.755 inches
Body Width:
Between 0.245 inches and 0.250 inches
Body Height:
Between 0.115 inches and 0.125 inches
Maximum Power Dissipation Rating:
180.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Dual edge triggered and monolithic and positive outputs and resettable and w/clear
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Diode-transistor logic and transistor-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 flip-flop, j-k, clocked and 2 flip-flop, j-k, master slave
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output and 50.00 nanoseconds.
output
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0