NSN 5962-00-253-7591

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-253-7591 **Body Length:** 0.830 inches **Body Width:** 0.280 inches **Body Height:** Between 0.140 inches and 0.180 inches **Operating Tempurature Range:** +0.0/+75.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and bipolar and w/disable and w/enable and positive outputs and w/storage **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 08783-37654870 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A458a0

Yes - demil/mli