NSN 5962-00-254-2368

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-254-2368

view Offiline at https://defobasegroup.com/nsi//0302-00-204-2000
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.260 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
300.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and high gain
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 amplifier, operational, general purpose
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Gold
Time Rating Per Chacteristic:
45.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminals gold and body gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:

A458a0