# NSN 5962-00-264-4499

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-264-4499

# **Body Length:**

Between 0.660 inches and 0.785 inches

# **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

# **Maximum Power Dissipation Rating:**

176.4 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+175.0 degrees celsius

#### **Features Provided:**

Monolithic and positive outputs and w/totem pole output

#### Inclosure Material:

Plastic

## Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Emitter-coupled logic

# Input Circuit Pattern:

Dual 2 wide 2 input

## **Design Function And Quantity:**

2 gate, and-or invert

## **Case Outline Source And Designator:**

T0-116 joint electron device engineering council

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

## Time Rating Per Chacteristic:

50.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level

output

# **Terminal Type And Quantity:**

14 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0