## NSN 5962-00-264-5057

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-264-5057 **Body Length:** Between 0.350 inches and 0.400 inches **Body Width:** Between 0.200 inches and 0.300 inches **Body Height:** Between 0.008 inches and 0.100 inches **Maximum Power Dissipation Rating:** 490.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and edge triggered and presettable and programmable and synchronous and **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 8 input **Case Outline Source And Designator:** -0-004-ag joint electron device engineering council **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output and 47.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Test Data Document:** 03640-6088564 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A458a0

No