NSN 5962-00-270-1778

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-00-270-1778

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

200.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs and medium power

Inclosure Material:

Glass and metal

Inclosure Configuration:

Input Circuit Pattern:

Can

Dual 2 input

Design Function And Quantity:

2 switch, analog

Case Outline Source And Designator:

T0-101 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

17.0 volts power source

Time Rating Per Chacteristic:

40000.00 nanoseconds propagation delay time, low to high level output and 40000.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

99380-0073-2104 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0