NSN 5962-00-276-9936

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-276-9936 **Body Length:** Between 0.815 inches and 0.890 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.155 inches and 0.180 inches **Maximum Power Dissipation Rating:** 560.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and positive outputs and complementary outputs and programmable and w/enable and w/open collector **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 converter, code binary coded decimal to binary **Case Outline Source And Designator:** -0-001-al joint electron device engineering council **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Special Features:** Static electricity sensitive **Precious Material And Location:** Terminals silver **Precious Material:** Silver Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-00-276-9936Digital Microcircuit - Page 2 of 2



Fiig:

A458a0