## NSN 5962-00-277-0237

Linear Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5962-00-277-0257
Body Length:
Between 0.390 inches and 0.410 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
High current and high speed and high voltage and internally compensated and monolithic and positive outputs
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, high current and 2 driver, peripheral
Terminal Surface Treatment:
Silver
Voltage Rating And Type Per Characteristic:
-1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level
output
Special Features:
Positive-or logic
Precious Material And Location:
Terminals silver
Precious Material:
Silver
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-00-277-0237

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0