NSN 5962-00-277-0237

Linear Microcircuit - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5962-00-277-0257 |
|--|
| Body Length: |
| Between 0.390 inches and 0.410 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| Between 0.140 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 800.0 milliwatts |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| High current and high speed and high voltage and internally compensated and monolithic and positive outputs |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| Dual 2 input |
| Design Function And Quantity: |
| 2 driver, high current and 2 driver, peripheral |
| Terminal Surface Treatment: |
| Silver |
| Voltage Rating And Type Per Characteristic: |
| -1.5 volts power source and 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level |
| output |
| Special Features: |
| Positive-or logic |
| Precious Material And Location: |
| Terminals silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 8 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

Yes - demil/mli

NSN 5962-00-277-0237

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0