## NSN 5962-00-284-6591

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-284-6591

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

#### **Body Height:**

Between 0.165 inches and 0.185 inches

### **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic and hermetically sealed and positive outputs and negative outputs and medium speed

#### **Inclosure Material:**

Glass and metal

#### **Inclosure Configuration:**

### Can

**Input Circuit Pattern:** 

4 input

#### **Criticality Code Justification:**

Feat

#### **Design Function And Quantity:**

1 comparator, voltage

#### **Case Outline Source And Designator:**

T0-99 joint electron device engineering council

#### **Terminal Surface Treatment:**

Gold

#### Voltage Rating And Type Per Characteristic:

15.0 volts power source

#### **Time Rating Per Chacteristic:**

200.00 nanoseconds propagation delay time, low to high level output

#### **Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L01341; for navy nuclear propulsion plant

products only

#### **Precious Material And Location:**

Terminal surfaces gold

#### **Precious Material:**

Gold

#### **Test Data Document:**

14933-I01341 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### **Terminal Type And Quantity:**

8 pin

#### Shelf Life:

N/a

# NSN 5962-00-284-6591

Linear Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

