## NSN 5962-00-284-6859

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-00-284-6859

View Online at https://aerobasegroup.com/nsn/5962-00-284-6859
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and hermetically sealed and positive outputs and externally compensated
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
4 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 regulator, voltage
Case Outline Source And Designator:
T0-99 joint electron device engineering council
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
50.0 volts power source
Special Features:
Item must comply with requirements of defense electronics supply center production standard n0.L01347; for navy nuclear propulsion plan
products only
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
14933-I01347 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:

\_\_

## NSN 5962-00-284-6859

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0