## NSN 5962-00-306-0939

Linear Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-00-306-0939  |
|--|
| Body Length:   |
| Between 0.745 inches and 0.785 inches                          |
| Body Width:  |
| Between 0.240 inches and 0.260 inches                          |
| Body Height:   |
| Between 0.150 inches and 0.180 inches                          |
| Maximum Power Dissipation Rating:                              |
| 300.0 milliwatts   |
| Operating Tempurature Range:                                   |
| +0.0/+70.0 degrees celsius                                     |
| Storage Tempurature Range:                                     |
| -65.0/+150.0 degrees celsius                                   |
| Features Provided:   |
| Adjustable and monolithic and positive outputs and synchronous |
| Inclosure Material:  |
| Plastic  |
| Inclosure Configuration:                                       |
| Dual-in-line   |
| Input Circuit Pattern:   |
| 12 input   |
| Design Function And Quantity:                                  |
| 1 phase locked loop  |
| Case Outline Source And Designator:                            |
| -0-001-ac joint electron device engineering council            |
| Terminal Surface Treatment:                                    |
| Solder   |
| Terminal Type And Quantity:                                    |
| 16 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |

A458a0