NSN 5962-00-308-9782



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-00-308-9782 **Body Length:** Between 0.660 inches and 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 198.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and positive outputs and w/totem pole output and high speed and schottky **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nand **Case Outline Source And Designator:** T0-116 joint electron device engineering council **Time Rating Per Chacteristic:** 4.50 nanoseconds propagation delay time, low to high level output and 5.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminals silver **Precious Material:** Silver Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0